



B614

BARRIER
24V ELECTROMECHANICAL

FAAC
Simply automatic.

When FAAC creates, it i

Modern design

Self-supporting polyester powder coated steel casing with a distinctive V shape. A compact design, but with a large internal space for wiring and for housing any optional accessories.

Maximum anti-crushing safety

A 24V motor with an integrated encoder provides a high degree of motion control and allows the reverse on obstacle safety standards to be met.

Robust, reliable, high performance

The exclusive use of high quality components and materials makes the B614 a robust and reliable operator. A quadrilateral lever system with two reduction stages makes beam movement even smoother.

Back up batteries

Installing the XBAT 24 module (high performance Nickel-Metal Hydride batteries), including battery charger, guarantees barrier operation even in the event of a mains power failure. (optional)

Beams

The beams, fitted with a rubber anti-impact profile, are available in both rectangular and rounded versions. Optional reflective stickers and LED lighting along the entire length of the beam (rounded or rectangular) make it easy to see even in conditions of poor visibility.



Innovates.

Dedicated and intuitive electronics

Electronic equipment, integrated in the upper part, protected by a coloured plastic cover that enhances the visibility of the LEDs. Intuitive programming via buttons and display. Wide choice of operating logics and configurable parameters. Integrated OMNIDEC universal radio decoding system. System protection and BUS 2Easy accessories simple to connect using only two non-polarised wires.

Integrated flashing traffic light

Optional high-visibility integrated flashing traffic light, to ensure complete traffic control. The operation of its high-efficiency red and green LEDs can be programmed via the board.

Complete range of accessories

Numerous accessories are available in order to personalise the product: beam lights and traffic light kit, hedge kit, joint kit, end foot and beam support fork.


Optimised logistics

Dimensions optimised for transport on pallets. Just a few sales codes to control passages of up to 5 m: only one version for right or left hand configuration; only one balancing spring, single or double mounted to balance the various beam lengths; beams and accessories common to other FAAC barrier ranges.

- Modern design
- Speed: 3m in less than 2s
- Maximum anti-crushing safety
- Easy to install



TECHNICAL CHARACTERISTICS

Power supply	220-240V ~ 50/60 Hz
Electric motor	24V  brushed
Max. power	165 W
Max. torque	300 Nm
Back-up batteries	Yes (optional)
Material	Steel
Surface treatment	Pre-hot dip galvanized, 20µm thick + polyester powder coated
Encoder	Incremental, integrated in the motor
Deceleration type	Electronic + mechanical
Beam type	Rectangular and rounded
Ambient operating temperature	-20°C to +55°C
Protection class	IP55 (Electronic control unit) - IP44
Weight	40 Kg
Use frequency	Continuous use
Electronic equipment	E614

The B614 increases the performance of electromechanical barriers. A newly designed barrier, aimed at meeting a wide range of requirements, from residential to commercial use.



HEADQUARTERS

ITALY

FAAC S.p.A. - Soc. Unipersonale
Via Calari 10 - 40069 Zola Predosa (BO)
Tel. +39 051 61724 - Fax +39 051 758518
it.info@faacgroup.com - www.faacgroup.com

SUBSIDIARIES

ASIA - PACIFIC

FAAC MALAYSIA
MAGNETIC CONTROL SYSTEMS SDN BHD
Selangor, Malaysia
tel. +60 3 5123 0033
www.faac.biz

AUSTRALIA

FAAC AUSTRALIA PTY LTD
Homebush – Sydney, Australia
tel. +61 2 87565644
www.faac.com.au

AUSTRIA

FAAC GMBH
Salzburg, Austria
tel. +43 662 85333950
www.faac.at

FAAC BV - TUBULAR MOTORS
Doetinchem, The Netherlands
tel. +49 30 5679 6645
faacbv.info@faacgroup.com
www.faac-tubularmotors.com

BENELUX

FAAC BENELUX NV/SA
Jabbeke, Belgium
tel. +32 50 320202
info@faacbenelux.com
www.faacbenelux.com

FAAC BV
Doetinchem, The Netherlands
tel. +31 314 369911
faacbv.info@faacgroup.com
www.faacbv.com

BRAZIL

INDÚSTRIAS ROSSI ELETROMECÂNICA LTDA
Brasília DF, Brazil
tel. +55 61 33998787
www.rossiportoes.com.br

CHINA

FAAC SHANGHAI
Shanghai, China
tel. +86 21 68182970
www.faacgroup.cn

FRANCE

FAAC FRANCE
Saint Priest - Lyon, France
tel. +33 4 72213020
www.faac.fr

FAAC FRANCE - AGENCE PARIS
Massy - Paris, France
tel. +33 4 72213020
www.faac.fr

FAAC FRANCE - DEPARTEMENT VOLETS
Saint Denis de Pile - Bordeaux, France
tel. +33 5 57551890
www.faac.fr

GERMANY

FAAC GMBH
Freilassing, Germany
tel. +49 8654 49810
www.faac.de

FAAC BV - TUBULAR MOTORS
Doetinchem, The Netherlands
tel. +49 30 5679 6645
faacbv.info@faacgroup.com
www.faac-tubularmotors.com

INDIA

FAAC INDIA
MAGNETIC AUTOCONTROL PVT LTD.
Chennai – India
Tel. +91 44 421 23297
info@magnetic-india.com
www.faac.biz

IRELAND

NATIONAL AUTOMATION LTD
Co. Roscommon, Ireland
tel. +353 71 9663893
www.nal.ie

MIDDLE EAST

FAAC MIDDLE EAST FZE
Dubai Silicon Oasis Operation Center - Dubai, UAE
tel. + 971 4 3724190
www.faac.ae

POLAND

FAAC POLSKA SP.ZO.O
Warszawa, Poland
tel. +48 22 8141422
fax +48 22 8142024
www.faac.pl

RUSSIA

FAAC RUSSIA
Moscow, Russia
tel. +7 (495) 646 24 29
www.faac.ru

SCANDINAVIA

FAAC NORDIC AB
Perstorp, Sweden
tel. +46 435 779500
www.faac.se

SOUTH AFRICA

CENTURION SYSTEMS PTY LTD
2162 Johannesburg
tel. +27 11 699 2400
www.centsys.co.za

SPAIN

CLEM, S.A.U.
San Sebastián de los Reyes - Madrid, Spain
tel. +34 91 3581110
www.faac.es

SWITZERLAND

FAAC AG
Altdorf, Switzerland
tel. +41 41 8713440
www.faac.ch

TURKEY

FAAC OTOMATİK GEÇİŞ SİSTEMLERİ
SAN. VE TİC. LTD. SİRKETİ
İstanbul, Turkey
tel. +90 (0)212 - 3431311
www.faac.com.tr

UNITED KINGDOM

FAAC UK LTD.
Basingstoke Hampshire, UK
tel. +44 1256 318100
www.faac.co.uk

U.S.A.

FAAC INTERNATIONAL INC
Rockledge, FL - U.S.A.
tel. +1 866 925 3222
www.faacusa.com

FAAC INTERNATIONAL INC
Fullerton, California - U.S.A.
tel. +1 714 446 9800
www.faacusa.com

FAAC S.p.A. - Soc. Unipersonale
Via Calari 10 - 40069 Zola Predosa (BO)
Tel. +39 051 61724 - Fax +39 051 0957820
it.info@faacgroup.com

FAAC
Simply automatic.